



Series:

2250

Wheel Offset Disk Harrow

For use with tractors in the 181 – 390hp range.



FEATURES:

- Uniquely designed harrow is available in five rigid and four wing fold models. Harrows are ideally suited to give excellent uniform tillage results in all light plowing applications.
- Mainframe, wings, and gang carriers constructed of tough high strength tubular steel for maximum strength and durability.
- Hydraulically controlled transport assembly with cylinder transport locks to pin wheels in raised position to safeguard implement from accidentally falling during transport.
- 10" (254mm) ground clearance with standard 28" (711mm) diameter disk blades.
- Adjustable gang angles of 18°, 20°, and 22° for both front and rear gangs.
- Up to 9" (229mm) maximum depth of penetration with standard 28" (711mm) diameter disk blades.
- Equipped with Timken dual tapered oil bath roller bearings.
- Standard bearing wear plates help protect the bearing housing from the wear caused by abrasive soils, extending their service life and decreasing cost.



Scan the bar code to visit
our website today:
www.romeplow.com



Specifications:

Series 2250 Wheel Offset Disk Harrow

11" (279mm) disk spacing; 1-5/8" (41mm) round axles; Equipped with Timken dual tapered roller bearings.

Model Number	Number of Disks	Number of Bearings	Width of Cut ft/in (m)	Transport Width ft/in (m)	Suggested Engine Horsepower	Weight Per Disks lbs (kg)	Net Weight lbs (kg)
2250-29	29	8	12'-4" (3.8)	13'-9" (4.2)	181 – 217	260 (118)	7540 (3420)
2250-33	33	12	14'-0" (4.3)	15'-11" (4.6)	207 – 243	258 (117)	8514 (3862)
2250-37	37	12	15'-8" (4.8)	17'-1" (5.2)	248 – 284	256 (116)	10,098 (4580)
2250-41	41	12	17'-5" (5.3)	18'-10" (5.7)	258 – 292	256 (116)	10,414 (4724)
2250-45	45	12	19'-2" (5.8)	20'-6" (6.3)	281 – 344	240 (109)	10,835 (4915)
2250-45-WF	45	16	19'-2" (5.8)	13'-6" (4.1)	281 – 344	301 (114)	13,534 (6151)
2250-49-WF	49	16	21'-0" (6.4)	13'-6" (4.1)	307 – 343	287 (113)	14,071 (6395)
2250-53-WF	53	16	22'-8" (6.9)	13'-6" (4.1)	329 – 365	285 (112)	15,125 (6875)
2250-57-WF	57	16	25'-2" (7.7)	13'-6" (4.1)	354 - 390	276 (111)	15,725 (7148)

*Engine horse powers are suggested ranges and vary according to soil conditions and weight added to harrow. Per ASAE S290.1 – Width of cut will vary with gang angle and disk blade diameter.

NOTE: This harrow requires hydraulic control. One rear tractor hydraulic circuit required for all rigid model 2250's. Two rear tractor hydraulic circuits required for all wing fold model 2250's.

Standard Equipment:

- 28" (711mm) diameter x 5/16" (8mm) thick, cutout (notched) shallow concavity disk blades.
- Heat treated alloy steel gang axles.
- Heavy duty fabricated steel spools.
- Heavy duty bearing wear plates.
- Tapered gang assemblies.
- Adjustable disk blade scrapers.
- Wheel hubs with 2 tapered roller bearings on each hub that are dust and moisture protected.
- Four dual 12L x 15 farm highway service tires for transporting, plowing, and turning.
- Hardened pins and bushings on all pivot points.
- Drawbar jack stand and safety chain.
- Hydraulic control group includes cylinders, hose holders, and hoses with fittings to reach rear of tractor.

Optional Equipment:

- 28" (711mm) diameter x 5/16" (8mm) thick; cutout (notched) front and smooth (round) rear shallow concavity disk blades.
- 28" (711mm) diameter x 5/16" (8mm) thick, cutout (notched) front and rear shallow concavity disk blades.
- 30" (762mm) diameter x 5/16" (8mm) thick, disk blades available in all 28" (711mm) configurations.
- Rear hitch assembly.
- Rear hitch hydraulic group.
- Extra heavy duty wear plates with 1/4" (6mm) hard plate overlay.



Rome Plow

475 Sixth Street

P.O. Box 48

Cedartown, GA 30125, USA

Telephone: 770.748.4450

Fax: 770.748.4427

Website: romeplow.com