

Series:

TRH-S

Woods Special Hinge Offset Disk Harrow For use with tractors in the 144 – 298hp range.



FEATURES:

- For deep plowing, and plowing after clearing.
- Special reinforcement for woods site preparation and other severe applications. Includes strengthened gang carriers, drawbar, offset bar, stabilizer, latch, bearing standards and bearing brackets.
- High gang carrier design to prevent trash build up and clogging.
- Adjustable disk blade scrapers.
- Equipped with Timken dual tapered roller bearings.
- Up to 647lbs (294kg) of weight per disk blade depending on model with an average of 608lbs (276kg).
- Up to 11" (279mm) maximum depth of penetration with standard 32" (813mm) diameter disk blades.



Scan the bar code to visit our website today:

www.romeplow.com



Specifications:

Series TRH-S Woods Special Hinge Offset Disk Harrow

14" (356mm) disk spacing: 2-1/2" (64mm) round axles; Equipped with Timken dual tapered roller bearings.

Model Number	Width of Cut	Number of Disks	Suggested Engine	Weight Per Disk	Net Weight
	ft/in (m)		Horsepower	lbs (kg)	lbs (kg)
TRH-14S	7'-6" (2.3)	14	144 – 169	645 (293)	9024 (4093)
TRH-16S	9'-0" (2.7)	16	165 – 190	647 (294)	10,344 (4692)
TRH-20S	11'-0" (3.4)	20	183 – 208	569 (258)	11,370 (5157)
TRH-24S	13'-6" (4.1)	24	229 – 253	582 (264)	13,975 (6339)
TRH-28S	15'-6" (4.7)	28	272 – 298	595 (270)	16,657 (7556)

^{*}Engine horsepowers are suggested ranges and vary according to soil conditions and weight added to harrow. Per ASAE S290.1 – Width of cut will vary with gang angle and disk blade diameter.

NOTE: This harrow requires hydraulic control. One rear tractor hydraulic circuit required for harrow operation.

Standard Equipment:

- 32" (813mm) diameter x 1/2" (13mm) thick, cutout (notched) deep concavity disk blades.
- Mechanical angling control.
- · Adjustable disk blade scrapers.
- Heat treated alloy steel gang axles.
- Heavy duty cast steel spacer spools.
- · Heavy duty bearing wear plates.
- Hydraulic control group includes cylinders, hose holders, and hoses with fittings to reach rear of tractor.
- · Drawbar jack stand and safety chain.

Optional Equipment:

- Cylinder rod stops.
- Weight box.



Rome Plow 475 Sixth Street P.O. Box 48

Cedartown, GA 30125, USA

Telephone: 770.748.4450

Fax: 770.748.4427

Website: romeplow.com