

Series: **TRCH**Hinge Offset Disk Harrow For upper with treators in the 165 - 240

For use with tractors in the 165 - 340 hp range.



FEATURES:

- For deep plowing, plowing in heavy trash, mixing and aerating.
- Heavy duty proven design with rugged boxed angle construction welded for maximum strength and rigidity.
- High gang carrier design to prevent trash build up and clogging.
- Adjustable disk blade scrapers.
- Equipped with Timken dual tapered roller bearings.
- Up to 850lbs (386kg) of weight per disk blade depending on model with an average of 775lbs (352kg).
- Up to 13" (330mm) maximum depth of penetration with standard 36" (914mm) diameter disk blades.
- Levels, cuts and mixes to full working depth.



Scan the bar code to visit our website today: www.romeplow.com



Specifications: Series TRCH Hinge Offset Disk Harrow

20" (508mm) disk spacing; 2-1/2" (64mm) round axles; Equipped with Timken dual tapered roller bearings.

Model Number	Width of Cut ft/in (m)	Number of Disks	Suggested Engine Horsepower	Weight Per Disk Ibs (kg)	Net Weight lbs (kg)
TRCH-10	7'-6" (2.3)	10	165 – 190	850 (386)	8496 (3854)
TRCH-12	9'-0" (2.7)	12	181 – 206	807 (366)	9680 (4391)
TRCH-16	12'-0" (3.7)	16	241 – 266	789 (358)	12,616 (5723)
TRCH-20	14'-0" (4.3)	20	280 - 304	729 (331)	14,582 (6614)
TRCH-24	18'-6" (5.6)	24	302 – 340	702 (318)	16,838 (7638)

*Engine horsepowers are suggested ranges and vary according to soil conditions and weight added to harrow. Per ASAE S290.1 – Width of cut will vary with gang angle and disk blade diameter.

NOTE: This harrow requires hydraulic control. One rear tractor hydraulic circuit required for harrow operation.

Standard Equipment:

- 36" (914mm) diameter x 1/2" (13mm) thick, cutout (notched) deep concavity disk blades.
- Mechanical angling control.
- Adjustable disk blade scrapers.
- Heat treated alloy steel gang axles.
- Heavy duty cast steel spacer spools.
- Heavy duty bearing wear plates.
- Hydraulic control group includes cylinders, hose holders, and hoses with fittings to reach rear of tractor.
- Drawbar jack stand and safety chain.

Optional Equipment:

- Cylinder rod stops.
- Weight box.



Rome Plow 475 Sixth Street P.O. Box 48 Cedartown, GA 30125, USA

Telephone: 770.748.4450 Fax: 770.748.4427 Website: romeplow.com