

ROME

Series:

TBW

Wheel Offset Disk Harrow

For use with tractors in the 49 – 183hp range.



FEATURES:

- Heavy duty proven design with rugged boxed angle construction welded for maximum strength and rigidity.
- High gang carrier design to prevent trash build up and clogging.
- Levels, cuts, and mixes to full working depth.
- Combines ease of maneuverability with high strength for the most adverse conditions.
- Up to 277lbs (126kg) of weight per disk blade depending on model with an average of 240lbs (109kg).
- Up to 9" (229mm) maximum depth of penetration with standard 26" (660mm) diameter disk blades.
- Equipped with Timken dual tapered roller bearings.
- Adjustable disk blade scrapers.
- Dual purpose transport unit for transportability and penetration control.



Scan the bar code to visit
our website today:
www.romeplow.com



Specifications:

Series TBW Wheel Offset Disk Harrow

11" (279mm) disk spacing; 1-5/8" (41mm) round axles; Equipped with Timken dual tapered roller bearings.

Model Number	Width of Cut ft/in (m)	Number of Disks	Suggested Engine Horsepower	Weight Per Disk lbs (kg)	Net Weight lbs (kg)
TBW-16	7'-0" (2.1)	16	49 – 74	252 (114)	4024 (1825)
TBW-20	8'-6" (2.6)	20	57 – 82	224 (102)	4490 (2037)
TBW-24	10'-6" (3.2)	24	69 – 94	223 (101)	5360 (2431)
TBW-28	12'-0" (3.7)	28	80 – 115	232 (105)	6490 (2944)
TBW-32	14'-0" (4.3)	32	102 – 126	233 (106)	7465 (3386)
TBW-40	18'-0" (5.5)	40	157 – 183	277 (126)	11,080 (5026)

*Engine horsepower are suggested ranges and vary according to soil conditions and weight added to harrow. Per ASAE S290.1 – Width of cut will vary with gang angle and disk blade diameter.

NOTE: This harrow requires hydraulic control. One rear tractor hydraulic circuit required for harrow operation.

Standard Equipment:

- Adjustable disk blade scrapers.
- 26" (610mm) diameter x 5/16" (8mm) thick; cutout (notched) deep concavity disk blades.
- Heat treated alloy steel gang axles.
- Heavy duty cast steel spacer spools.
- Heavy duty bearing wear plates.
- New industrial tires – 2 each. TBW-16: 7.5 x 16 – 6 ply. TBW-20 and TBW-24: 7.5 x 16 – 10 ply. TBW-32: 12.5L x 15 – 12 ply. TBW-40: 16.5L x 16.1 – 10 ply.

- Hydraulic control group includes cylinders, hose holders, and hoses with fittings to reach rear of tractor.
- Two heavy duty gang wrenches.
- Drawbar jack stand and safety chain.

Optional Equipment:

- 28" (711mm) diameter x 5/16" (8mm) thick, cutout (notched) deep concavity disk blades.
- Drawbar with track type clevis.
- Cylinder rod stops for positive depth control adjustment.



Rome Plow

475 Sixth Street

P.O. Box 48

Cedartown, GA 30125, USA

Telephone: 770.748.4450

Fax: 770.748.4427

Website: romeplow.com